



Pumpfix F / Staufix FKA / Staufix SWA			Accessories
Illustration and dimensioned drawing	Article description	Outer diameter Ø (mm)	Article #
<p>For models made on or after Jan 2011</p> 	<p>Conversion kit Pumpfix F With 5 m cable length</p> <p>1 Pumpfix F Komfort incl. Komfort control unit with recessed cover for on-site tiling and drain, class A 15, incl. <i>Multistop</i> incl. gasket for installation in a concrete slab/floor</p> <p>2 Pumpfix F Komfort incl. Komfort control unit for installation in an exposed wastewater pipe</p>	<p>Ø 110-200*</p>	<p>80 098</p>
	<p>Conversion kit Staufix FKA Komfort With 5 m cable length incl. Komfort control unit for installation in a concrete slab/floor and in an exposed wastewater pipe</p>	<p>Ø 110-200*</p>	<p>80 093</p>
<p>For models made on or after Jan 2011</p> 	<p>Conversion kit Staufix SWA for installation in a concrete slab/floor and in an exposed wastewater pipe</p>	<p>Ø 110-200*</p>	<p>80 091</p>



Simple retrofitting:

Within the complete series, all backwater protection components from **the drain body / clean out Controlfix** to the **Pumpfix F** backwater valve with integrated pump can be retrofitted easily later into the installed chamber, without tools being necessary.



Clean out
Controlfix

Twin flap
backwater valve
Staufix SWA

Backwater valve
Staufix FKA

Backwater pumping
station *Pumpfix F
Komfort-Version*

<p>For models made on or after Jan 2011</p> 	<p>Rat protection flap with stainless steel shield for <i>Staufix FKA Komfort</i> (with flap in pendulum position) and <i>Staufix SWA</i></p>	-	<p>80 037</p>
	<p>Testing funnel with sealing gasket for servicing all <i>Staufix</i> backwater valves, suitable for Ø 110, 125, 160</p>	-	<p>70 214</p>