Drains



□ 132

in ABS, vertical and lateral adjustable, incl. mesh fabric

with design cover Kessel □ 120 mm and rim in stainless steel AISI 304, class L 15. For tile thickness of 8-21 mm, Lock & Lift System

Art. # 47 904

with design cover *Oval* □ 120 mm and rim in stainless steel AISI 304, class L 15. For tile thickness of 8-21 mm, Lock & Lift System

Art. # 47 905





















in ABS

design covers □ 120 mm and rim in stainless steel AISI 304, class K 3 / L 15 with or without Lock & Lift System.

		Kessel (CI.L 15)	Oval (Cl. L 15)	Spot (CI. K 3)	Cross (CI.K 3)	Festival (CI.K 3)	Parade (CI. K 3)	Slot (CI. K 3)	Sticks (CI.K 3)	
with Lock & Lift	Art. #	27 201	27 202	27 221	27 213	27 215	27 224	27 219	27 217	
without Lock & Lift	Art. #	27 225	27 226	27 220	27 212	27 214	27 223	27 218	27 216	















Conversion kit,

for article: 37 3001

Consist of

"DIN push-fit connection"

1 outlet adapter Ø 75 mm and 1 push-fit connection



Intermediate section with glue flange Multistop

in ABS, for shallow bed gasket incl. mesh fabric, Art. # 47 900





odour, foam, rodent and insect stop

Art. # 43 500



Transition section

with sealing ring \emptyset 50

Ø 50/75 Art. # 27 126



Ø 50/40 Art. # 27 118 3 inlet adapter Ø 50 mm,

for upper section \emptyset 110, EN 1451-1 Art. # 37 3008

Conversion kit, "DIN glue connection"

for article: 37 3001 Consist of 3 inlet adapter Ø 50 mm, and 1 outlet adapter \varnothing 75, EN 1451-1

Art. # 37 3007

Extension section

in ABS, with lip seal Art. # 27 146

Hair filter


made of polymer, Ø 108 mm made of polymer


Art. # 43 700

Sludge trap


Art.# 27 168

0.8 l/sec flow rate *) Sealing water height 30 mm














Bathroom drain "The Superflat" in PP

Lateral outlet \varnothing **50**, with removable odour trap

Without lateral inlet Art. # 42 700

One lateral inlet Ø 40 Art. # 42 701

Three lateral inlets \emptyset 40

Art. # 42 703