

Basement drains	Products		
Illustration and dimensioned drawing	Article description	Outer diameter Ø (mm)	Article #
  <p>1.6 l/sec flow rate Installation area 220 x 280 mm</p>	<p><b>Basement drain in PP</b> <b>Lateral outlet 2.5°, with removable odour trap and sludge trap.</b> <b>With upper section in PP</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> with slotted cover 150 x 150 mm made of polymer, black. <b>Class K 3</b> (able to withstand loads up to max. 300 kg).</li> </ul>	<p>Ø 110</p>	<p><b>36 501</b></p>
  <p>1.8 l/sec flow rate Installation area 220 x 180 mm</p>  <p>1.8 l/sec flow rate Installation area 180 x 180 mm</p>	<p><b>Basement drain in PP</b> <b>With removable odour trap</b> With lip seal and protective cover for use during construction. <b>With upper section in ABS</b> <b>Lateral outlet 2.5°</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> with slotted cover 138 x 138 mm in ABS, black. <b>Class K 3</b> (able to withstand loads up to max. 300 kg).</li> </ul> <p><b>Vertical outlet</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> with slotted cover 138 x 138 mm in ABS, black. <b>Class K 3</b> (able to withstand loads up to max. 300 kg).</li> </ul>   <p>EN 1253</p>	<p>Ø 110</p> <p>Ø 110</p>	<p><b>45 110.40</b></p> <p><b>45 210.40</b></p>
  <p>1.8 l/sec flow rate Installation area 220 x 180 mm</p>  <p>1.8 l/sec flow rate Installation area 180 x 180 mm</p>	<p><b>Basement drain in PP</b> <b>Without removable odour trap, with sludge trap</b> With lip seal and protective cover for use during construction. <b>With upper section in ABS</b> <b>Lateral outlet 2.5°</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> with slotted cover 138 x 138 mm in ABS, black. <b>Class K 3</b> (able to withstand loads up to max. 300 kg).</li> </ul> <p><b>Vertical outlet</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> with slotted cover 138 x 138 mm in ABS, black. <b>Class K 3</b> (able to withstand loads up to max. 300 kg).</li> </ul>	<p>Ø 110</p> <p>Ø 110</p>	<p><b>34 101</b></p> <p><b>34 102</b></p>