

Floor drains Ferrofix with connection flange

Matrix order system / Products

Drain body	Upper sections			
Floor drain Ferrofix in stainless steel AISI 304 with connection flange with odour trap, connection to SML-pipe	Shallow bed upper section in ABS, with mesh fabric	Shallow bed upper section in ABS, with mesh fabric	Upper section in ABS	Upper section in stainless steel AISI 304
90 0 90 0	Ø 312 □ 150 □ 150 021 ■ Ø 125 ■	312 0150 0125-1 021 021 0312 0312 0312 0312 0312 0312	□ 150 □ 150 □ 150 □ 150 □ 150	S
0142- 0132- 010	with slotted cover 138 x 138 mm and rim in stainless steel AISI 304, non-slip, class L 15, screwed Art. # 48 907	with anti-slip drain cover 138 x 138 mm and rim in stainless steel AISI 304, non-slip, class L 15 Art. # 48 965	with slotted cover 138 x 138 mm and rim in stainless steel AISI 304, non-slip, class L 15, screwed Art. # 48176	with anti-slip drain cover 138 x 138 mm in stainless steel AISI 304, class L 15 / M 125* * On-site lining work required Art. # 54 914
Ø 78	Complete drain comprising a combination of the drain body and upper section			
Lateral outlet Art. # 54 400	54 400.52	54 400.21	54 400.61	54 400.20
Vertical outlet Art. # 54 410	54 410.52	54 410.21	54 410.61	54 410.20
Ø 110	Complete drain comprising a combination of the drain body and upper section			
Lateral outlet Art. # 54 420	54 420.52	54 420.21	54 420.61	54 420.20
Vertical outlet Art. # 54 430	54 430.52	54 430.21	54 430.61	54 430.20

^{*} Draining capacity valid for \varnothing 110 vertical outlet. Other variants 1.8 l/sec.





Drains / channels in stainless steel

Accessories see page 218