Balcony drains			Products
Illustration and dimensioned drawing	Article description	Outer diameter ∅ (mm)	Article #
	Balcony drain in ABS Frost-proof outlet. With fixed lip seal. With glue flange and counter flange.		
9	■ Lateral outlet	■ Ø 50	40 151.90
Ø332 0332 0332 0332 0332 0332 0332 0332 0332 0332	2 Vertical outlet With upper section in ABS with slotted cover 100 x 100 mm in stainless steel AISI 304, class K3 (able to withstand loads up to max. 300 kg).	2 ∅ 50	40 251.90
0.9 l/sec flow rate Installation area 180 x 180 mm			
0.9 l/sec flow rate Installation area 220 x 180 mm	Balcony drain in ABS Frost-proof outlet. With fixed lip seal. With connection flange. □ Lateral outlet With upper section in ABS with slotted cover 100 x 100 mm in stainless steel AISI 304, class K3 (able to withstand loads up to max. 300 kg).	Ø 50 Ø 75	40 151.20 40 171.20
0.9 l/sec flow rate Installation area 220 x 180 mm	Balcony drain in ABS Frost-proof outlet. With connection flange. □ Lateral outlet with inserted cover Ø 125 in synthetic material, class K3 (able to withstand loads up to max. 300 kg)	Ø 50 Ø 75	40 152.71 40 172.71

Balcony drains			Accessories
Illustration and dimensioned drawing	Article description	Outer diameter ∅ (mm)	Article #
Ø125 Ø 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Extension section in ABS, with lip seal	-	27 146
Ø105 ₩	Multistop rodent, insect, foam and odour stop	-	43 500