

# Grease separators for underground installation

## Grease separator in accordance with EN 1825

## Accessories

Illustration and dimensioned drawing	Article description	Outer diameter Ø (mm)	Article #
	<p><b>SonicControl level sensing system with ultra sonic sensor for grease separator</b> Accurate monitoring and data transfer of grease levels. 230 V - 50 Hz power connection. With battery back up, connection for remote speaker. Installation set with easy assembly and maintenance. For use on above ground or below ground separators. For retrofit use on existing separators. Control unit with optical and audible alarm with potential free contact. Electronic log book with 12 month capacity. Data transfer by telemetry.</p> <p>Voltage: 230 V ~ 50 Hz Protection: IP 54 Plug: Schuko 1.5 m Cable length: 10 m (extendable on-site to 60 meters)</p> <p><b>Accessories</b> Audible alarm Art. # 20 162, 25 m cable extension available upon request. PE-HD Cable access conduit Art. # 917 822</p>	-	<b>917 821</b>
	<p><b>Cable extension set for SonicControl</b></p> <p><input type="checkbox"/> 10 m extension</p> <p><input type="checkbox"/> 20 m extension</p> <p><input type="checkbox"/> 30 m extension</p>	-	<b>917 871</b> <b>917 872</b> <b>917 873</b>
	<p><b>Cable access conduit</b> Required for watertight connection of <i>SonicControl</i> cable into separator chamber (for underground separators a conduit pipe with chase wire should be planned)</p>	-	<b>917 822</b>
	<p><b>TeleControl telemetric system</b> for connection to KESSEL Comfort control units (lifting stations and separators) 230 Volt and 400 Volt. Relaying of full text messages to up to three mobile phones. Without SIM card.</p>	-	<b>28 792</b>
	<p><b>TeleControl antenna booster</b> for <i>TeleControl</i> telemetric system incl. 2.5 m cable to improve reception. With magnetic base.</p>	-	<b>28 793</b>
	<p><b>Antenna booster extension cable</b> cable length 2.5 m</p>	-	<b>28 794</b>
	<p><b>Stainless steel access panel</b> For recessed wall installation with Storz-B disposal pipe hook up connection and remote control connection for use with fully automated grease separators. Remote control not included. Dimensions: 640 x 440 x 160 mm (Width x Height x Depth) <b>Model: "Recessed"</b>, 2 doors, lockable</p>	-	<b>917 414</b>
	<p><b>Stainless steel access panel</b> For wall installation with Storz-B disposal pipe hook-up connection and remote control connection for use with fully automated grease separators. Remote control not included. Dimensions: 600 x 400 x 160 mm (Width x Height x Depth) <b>Model: "Wall installation"</b>, 2 doors, lockable</p>	-	<b>917 413</b>