



Backwater protection
1

Staufix Ø 50 / Staufix Ø 75 / Staufix Siphon Ø 50			
Illustration and dimensioned drawing	Article description	Outer diameter Ø (mm)	Article #
	<p>Twin flap backwater valve Staufix Ø 50 made of polymer for exposed wastewater pipes</p> <p>Twin flaps, self-closing, one of which can be locked by hand as an emergency closure. Inlet/outlet for connection to HT-pipe according to EN 1451-1.</p> <p>CE EN 13564 Type 2</p>	Ø 50	73050
	<p>Twin flap backwater valve Staufix Ø 75 made of polymer for exposed wastewater pipes</p> <p>Twin flaps, self-closing, one of which can be locked by hand as an emergency closure. Inlet/outlet for connection to HT-pipe according to EN 1451-1.</p> <p>CE EN 13564 Type 2</p>	Ø 75	73070
	<p>Twin flap backwater valve Staufix Siphon Ø 50 made of polymer for washing stand siphons</p> <p>Twin flaps, self-closing, one of which can be locked by hand as an emergency closure, incl. wall attachment, inlet connection Ø 40 (1 1/2 inch) at pipe odour trap. Outlet Ø 50 for connection to HT-pipe according to EN 1451-1.</p> <p>CE EN 13564 Type 5</p>	Ø 50	73051
	<p>Twin flap backwater valve Staufix Siphon Ø 50 made of polymer Model with pipe odour trap and washing machine connection</p> <p>Twin flaps, self-closing, one of which can be locked by hand as an emergency closure, incl. wall attachment, outlet Ø 50 for connection to HT-pipe according to EN 1451-1.</p> <p>CE EN 13564 Type 5</p>	Ø 50	73052
	<p>Twin flap backwater valve Staufix Siphon Ø 50 made of polymer Model with pipe odour trap and inlet funnel, ideal for the emergency overflow of heating systems</p> <p>Two flaps, self-closing, one of which can be locked by hand as an emergency closure, incl. wall attachment. Outlet Ø 50 for connection to an HT-pipe according to EN 1451-1.</p> <p>CE EN 13564 Type 5</p>	Ø 50	73053

Backwater valves for wastewater without sewage

Installation example *Staufix* Ø 50 / Ø 75 / *Staufix Siphon* Ø 50



Multiple applications . . . Ø 50 or Ø 75 exposed drainage pipe



... washbasins with odour traps



... washbasins with odour traps and washing machine connection



... furnace condensation overflow

Professional advantages

- Preventative backwater protection in new construction - also excellent for renovation.
- Unique twin flap system according to Norm.
- Quick and problem free installation.
- Prevents flooding from additional wastewater drainage pipes connected to same drainage system.
- Easy maintenance and service with tool free finger clips.
- Complete polymer construction - no more rust.
- Also usable for rodent protection.