










Aqualift F Compact		Accessories																										
Illustration and dimensioned drawing	Article description	Outer diameter Ø (mm)	Article #																									
 <p>Waterproof concrete installation tested by MFPA Leipzig UB 5.1/11-452-1</p>	<p>Gasket set for installation in waterproof concrete</p> <p>Consisting of: Counter flange made of polymer, incl. screws, elastomer waterproof membrane in NK/SBR Ø 800 mm for article numbers: 28 701-C, 28 704-C</p>	-	83 023																									
	<p>Pressure pipe set Incl. 5 m pressure pipe hose Ø 40 for article numbers: 28 701-C, 28 704-C, 28 711-C, 28 743-C</p>	Ø 40	28 040																									
	<p>Audible alarm <input type="checkbox"/> 20 m cable length suitable for all control units</p>	-	20 162																									
	<p>Potential-free contact for all Aqualift 230 V Comfort control units</p>	-	80 072																									
	<p>Compressor set for use in combination with lifting stations and pumping stations with pressure control: <input type="checkbox"/> prevents soiling, compensates leaks, avoids condensate forming in the pressure hose, makes operation of systems possible with pressure hose lengths > 10 m, including connection T-piece, including 20 m pressure hose.</p>	-	28 048																									
	<p>PE-pressure hose extension (bulk goods)</p>	-	680 071																									
	<p>Retrofit kit alarm float switch for lifting stations Aqualift F Compact Can be combined with 230 V Comfort control units. Comprises a float switch, float switch bracket and 5 m connection cable.</p>	-	28 016																									
	<p>TeleControl telemetric system for connection to KESSEL Comfort control units 230 Volt and 400 Volt. Relaying of full text messages to up to three mobile phones. Without SIM card.</p>	-	28 792																									
	<p>TeleControl antenna booster for TeleControl telemetric system incl. 2.5 m cable to improve reception. With magnetic base.</p>	-	28 793																									
	<p>Antenna booster extension cable cable length 2.5 m</p>	-	28 794																									
	<p>1 Cable extension for probe 10 m cable length</p>	-	80 889																									
	<p>2 Cable extension for pump 10 m cable length</p>	-	80 891																									
	<p>Explanation of cable extensions:</p> <table border="1"> <thead> <tr> <th></th> <th colspan="2">Extension to 15 m</th> <th colspan="2">Extension to 25 m</th> </tr> </thead> <tbody> <tr> <td><i>Aqualift F Compact Mono</i> Cable length delivered 5 m</td> <td>1</td> <td>1 x 80 889</td> <td>1</td> <td>2 x 80 889</td> </tr> <tr> <td></td> <td>2</td> <td>1 x 80 891</td> <td>2</td> <td>2 x 80 891</td> </tr> <tr> <td><i>Aqualift F Compact Duo</i> Cable length delivered 5 m</td> <td>1</td> <td>1 x 80 890</td> <td>1</td> <td>2 x 80 890</td> </tr> <tr> <td></td> <td>2</td> <td>2 x 80 889</td> <td>2</td> <td>4 x 80 889</td> </tr> </tbody> </table>		Extension to 15 m		Extension to 25 m		<i>Aqualift F Compact Mono</i> Cable length delivered 5 m	1	1 x 80 889	1	2 x 80 889		2	1 x 80 891	2	2 x 80 891	<i>Aqualift F Compact Duo</i> Cable length delivered 5 m	1	1 x 80 890	1	2 x 80 890		2	2 x 80 889	2	4 x 80 889		
	Extension to 15 m		Extension to 25 m																									
<i>Aqualift F Compact Mono</i> Cable length delivered 5 m	1	1 x 80 889	1	2 x 80 889																								
	2	1 x 80 891	2	2 x 80 891																								
<i>Aqualift F Compact Duo</i> Cable length delivered 5 m	1	1 x 80 890	1	2 x 80 890																								
	2	2 x 80 889	2	4 x 80 889																								