

Aqualift S / Minilift		Accessories										
Illustration and dimensioned drawing	Article description	Outer diameter Ø (mm)	Article #									
 <p>Waterproof concrete installation tested by MFPA Leipzig UB 5.1/11-452-1</p>	<p>Gasket set for installation in waterproof concrete</p> <p>Consisting of: Counter flange made of polymer, incl. screws, elastomer waterproof membrane in NK/SBR Ø 800 mm</p> <p>for article numbers: 28 500, 28 550-C, 28 530-C</p>	-	83 023									
	<p>Cover plate Class A 15</p> <p><input type="checkbox"/> grey</p> <p><input type="checkbox"/> black</p> <p>for article numbers: 28 570</p>	-	30 003 W 30 003 S									
	<p>Cover with grating Class A 15</p> <p><input type="checkbox"/> grey</p> <p><input type="checkbox"/> black</p> <p>for article numbers: 28 570</p>	-	30 001 W 30 001 S									
	<p>Extension section made of polymer</p> <p>Height = 220 mm for deep installation</p> <p>for article numbers: 28 570</p>	-	32 500									
	<p>Alarm</p> <p><input type="checkbox"/> with electrode probe</p> <p><input type="checkbox"/> with optical probe</p> <p>for article numbers: 28 500</p>	-	20 220 20 221									
	<p>1 Audible alarm</p> <p><input type="checkbox"/> 20 m cable length</p> <p>2 Potential-free contact</p> <p>for all Aqualift 230 V Comfort control units</p>	-	20 162 80 072									
	<p>Pressure pipe set incl. 5 m pressure pipe hose Ø 40</p> <p>for article numbers: 28 500, 28 550-C, 28 530-C</p>	Ø 40	28 040									
	<p>Hole saw Ø 50, 75, 110 (Saw blade holder Ø = 145 mm)</p> <p>Hole saw Ø 50, 75, 110, 125 and 160 (Saw blade holder Ø = 190 mm)</p>	-	50 101 50 100									
	<p>Pipe sealing gasket (EPDM)</p> <p>Use KESSEL hole saw when drilling.</p> <p>for article numbers: 28 500, 28 550-C, 28 530-C, 28 560, 28 541-C</p>	Ø 50 Ø 75 Ø 110 Ø 125 Ø 160	850 114 850 116 850 117 850 118 850 119									
	<p>1 Cable extension for probe 10 m cable length</p> <p>2 Cable extension for pump 10 m cable length</p> <p>Explanation of cable extensions:</p>	-	80 889 80 891									
			<table border="1"> <thead> <tr> <th></th> <th>Extension to 15 m</th> <th>Extension to 25 m</th> </tr> </thead> <tbody> <tr> <td>Aqualift S Tronic Art. # 28 550-C Cable length delivered 5 m</td> <td>1 1 x 80 889 2 1 x 80 891</td> <td>1 2 x 80 889 2 2 x 80 891</td> </tr> <tr> <td>Aqualift S Art. # 28 530-C and 28 541-C Cable length delivered 5 m</td> <td>1 1 x 80 890 2 2 x 80 889</td> <td>1 2 x 80 890 2 4 x 80 889</td> </tr> </tbody> </table>		Extension to 15 m	Extension to 25 m	Aqualift S Tronic Art. # 28 550-C Cable length delivered 5 m	1 1 x 80 889 2 1 x 80 891	1 2 x 80 889 2 2 x 80 891	Aqualift S Art. # 28 530-C and 28 541-C Cable length delivered 5 m	1 1 x 80 890 2 2 x 80 889	1 2 x 80 890 2 4 x 80 889
	Extension to 15 m	Extension to 25 m										
Aqualift S Tronic Art. # 28 550-C Cable length delivered 5 m	1 1 x 80 889 2 1 x 80 891	1 2 x 80 889 2 2 x 80 891										
Aqualift S Art. # 28 530-C and 28 541-C Cable length delivered 5 m	1 1 x 80 890 2 2 x 80 889	1 2 x 80 890 2 4 x 80 889										