

Pumping stations for wastewater with or without sewage

System chambers Ø 1000

With access opening Ø 600 / Ø 800 mm

Illustration and dimensioned drawing

Article description

Installation depth mm

Article #

For underground installation




Illustration shows 1 2

Engineering system chamber for combination with engineering system base Aqualift F XL- and Aqualift S XL for underground installation

made of polyethylene

with access opening Ø 600 mm

Upper section with round cover

1 made of cast iron, class A/B

2 made of cast iron, class D

1	D 1:	380 - 629*	874 00 00
	D 2:	630 - 879*	874 00 06
	D 3:	880 - 1129*	874 00 12
	D 4:	1130 - 1379	874 00 18
	D 5:	1380 - 1629	874 00 24
	D 6:	1630 - 1879	874 00 30
	D 7:	1880 - 2129	874 00 36
	D 8:	2130 - 2379	874 00 42
	D 9:	2380 - 2629	874 00 48
	D 10:	2630 - 2879	874 00 54
	D 11:	2880 - 3129	874 00 60
	D 12:	3130 - 3379	874 00 66
	D 13:	3380 - 3629	874 00 72
	D 14:	3630 - 3879	874 00 78
	D 15:	3880 - 4129	874 00 84

2	D 1:	380 - 629*	874 00 01
	D 2:	630 - 879*	874 00 07
	D 3:	880 - 1129*	874 00 13
	D 4:	1130 - 1379	874 00 19
	D 5:	1380 - 1629	874 00 25
	D 6:	1630 - 1879	874 00 31
	D 7:	1880 - 2129	874 00 37
	D 8:	2130 - 2379	874 00 43
	D 9:	2380 - 2629	874 00 49
	D 10:	2630 - 2879	874 00 55
	D 11:	2880 - 3129	874 00 61
	D 12:	3130 - 3379	874 00 67
	D 13:	3380 - 3629	874 00 73
	D 14:	3630 - 3879	874 00 79
	D 15:	3880 - 4129	874 00 85

For underground installation

NEW




Illustration shows 4 5

with access opening Ø 800 mm

Upper section with round cover

3 made of stainless steel, class K 3

Upper section with square cover,

4 made of stainless steel, class B 15,

5 made of stainless steel, class D 15,

3	D 1:	375 - 624*	874 01 22
	D 2:	625 - 874*	874 01 23
	D 3:	875 - 1124*	874 01 24
	D 4:	1125 - 1374	874 01 25
	D 5:	1375 - 1624	874 01 26
	D 6:	1625 - 1874	874 01 27
	D 7:	1875 - 2124	874 01 28
	D 8:	2125 - 2374	874 01 29
	D 9:	2375 - 2624	874 01 30
	D 10:	2625 - 2874	874 01 31
	D 11:	2875 - 3124	874 01 32
	D 12:	3125 - 3374	874 01 33
	D 13:	3375 - 3624	874 01 34
	D 14:	3625 - 3874	874 01 35
	D 15:	3875 - 4124	874 01 36

4	D 1:	620 - 869*	874 01 41
	D 2:	870 - 1119*	874 01 42
	D 3:	1120 - 1369*	874 01 43

5	D 1:	620 - 869*	874 01 58
	D 2:	870 - 1119*	874 01 59
	D 3:	1120 - 1369*	874 01 60

Covers surface water tight

Handles groundwater depths up to 3000 mm

Delivered as individual elements

Removable access aid article # 860 126 on request

Other installation depths
on request

**In compliance with EN 13598 Part 2
Certification: Z-42.1-527**

* Installation depth D 1 - D 3
only in combination with pumping station
Wet installation

** Installation depth D 12 - D 15
pay attention to maximum installation depth
5000 mm in combination with engineering
system base