

# Submersible pumps for wastewater with or without sewage



## KTP 300

Illustration and dimensioned drawing	Article description	Pressure connection	Article #																		
	<p><b>Submersible pump KTP 300</b> for wastewater without sewage <b>with/without</b> float switch</p> <p>With backwater flap, pivotable connection, cable length 10 m</p> <p><input type="checkbox"/> <b>without float switch</b></p> <p><input type="checkbox"/> <b>with float switch</b></p> <p>Input power (P1): 280 W. Voltage: 230 V ~ 50 Hz. Max. pumping height: 6 m. Max. pumping capacity: 8 m<sup>3</sup>/h. Max. submersible depth: 10 m. max. particle size: 10 mm. Pressure connection: 1 inch side / vertical</p> <p>Removable input basket - reduction in the water level to 8 mm possible.</p>	1 inch	<b>28 740</b>																		
		1 inch	<b>28 840</b>																		
			<table border="1"> <thead> <tr> <th colspan="2">KTP 300</th> </tr> </thead> <tbody> <tr> <td>Current type</td> <td>Alternating current</td> </tr> <tr> <td>Voltage</td> <td>230 V</td> </tr> <tr> <td>Current</td> <td>1.9 A</td> </tr> <tr> <td>Power P1/P2</td> <td>280 W / 114 W</td> </tr> <tr> <td>RPM</td> <td>2800 min<sup>-1</sup></td> </tr> <tr> <td>Motor protection</td> <td>integrated</td> </tr> <tr> <td>Plug</td> <td>Schuko</td> </tr> <tr> <td>Operating mode</td> <td>S1</td> </tr> </tbody> </table>	KTP 300		Current type	Alternating current	Voltage	230 V	Current	1.9 A	Power P1/P2	280 W / 114 W	RPM	2800 min <sup>-1</sup>	Motor protection	integrated	Plug	Schuko	Operating mode	S1
KTP 300																					
Current type	Alternating current																				
Voltage	230 V																				
Current	1.9 A																				
Power P1/P2	280 W / 114 W																				
RPM	2800 min <sup>-1</sup>																				
Motor protection	integrated																				
Plug	Schuko																				
Operating mode	S1																				

## STZ 1000



Illustration and dimensioned drawing	Article description	Pressure connection	Article #																
	<p><b>Submersible pump STZ 1000</b> for wastewater containing raw sewage <b>with/without</b> float switch <b>with</b> macerator.</p> <p>Connection to pressure pipe 1 1/4 inch. Outlet side / vertical, cable length 10 m</p> <p><input type="checkbox"/> <b>without float switch</b></p> <p><input type="checkbox"/> <b>with float switch</b></p> <p>Voltage: 230 V ~ 50 Hz Input power (P1): 1080 W Max. pumping height: 10 m Max. pumping capacity: 12 m<sup>3</sup>/h Max. submersible depth: 10 m Pressure connection: 1 1/4 inch side / vertical</p>	1 1/4 inch	<b>28 779</b>																
		1 1/4 inch	<b>28 778</b>																
			<table border="1"> <thead> <tr> <th colspan="2">STZ 1000</th> </tr> </thead> <tbody> <tr> <td>Current type</td> <td>Alternating current</td> </tr> <tr> <td>Voltage</td> <td>230 V</td> </tr> <tr> <td>Current</td> <td>4.9 A</td> </tr> <tr> <td>Power P1/P2</td> <td>1080 W / 620 W</td> </tr> <tr> <td>RPM</td> <td>2800 min<sup>-1</sup></td> </tr> <tr> <td>Motor protection</td> <td>integrated</td> </tr> <tr> <td>Operating mode</td> <td>S3 - 30 %</td> </tr> </tbody> </table>	STZ 1000		Current type	Alternating current	Voltage	230 V	Current	4.9 A	Power P1/P2	1080 W / 620 W	RPM	2800 min <sup>-1</sup>	Motor protection	integrated	Operating mode	S3 - 30 %
STZ 1000																			
Current type	Alternating current																		
Voltage	230 V																		
Current	4.9 A																		
Power P1/P2	1080 W / 620 W																		
RPM	2800 min <sup>-1</sup>																		
Motor protection	integrated																		
Operating mode	S3 - 30 %																		