1.8 l/sec / 1.1 l/sec* flow rate
Sealing water height 50 mm

Project drains *Ecoguss* with pressure sealing flange — Matrix order system

Drain body	Upper sections			
Ecoguss **with pressure sealing flange** for connection to SML-pipe, with odour trap 50 mm	**Shallow bed upper section in ABS,** with mesh fabric	**Shallow bed upper section in ABS,** with mesh fabric	**Upper section in ABS**	**Upper section in ABS**
   ∅ 58 / 78 / 83 / 110 B 245 / 134 / 134 / 148 H 120 / 109 / 108 / 92				
With slotted cover 138 x 138 mm and rim in stainless steel AISI 304, class L 15, screwed Art. # **48 963**	**With design cover** ***Kessel*** 120 x 120 mm and rim in stainless steel AISI 304, class L 15, *Lock & Lift* System Art. # **48 904**	**With design cover** ***Kessel*** 120 x 120 mm, and rim in stainless steel AISI 304, class L 15, *Lock & Lift* System Art. # **48 201**	**With slotted cover** 138 x 138 mm in stainless steel AISI 304, class K 3, screwed Art. # **48 950**
   ∅ 58 / 78 / 83 / 110 H 100 / 110 / 110 / 110				
∅ 58	**Complete drain comprising a combination of the drain body and upper section**			
Lateral outlet Art. # **48 758**	**48 758.51**	**48 758.53**	**48 758.63**	**48 758.11**
Vertical outlet Art. # **48 858**	**48 858.51**	**48 858.53**	**48 858.63**	**48 858.11**
∅ 78				
Lateral outlet Art. # **48 778**	**48 778.51**	**48 778.53**	**48 778.63**	**48 778.11**
Vertical outlet Art. # **48 878**	**48 878.51**	**48 878.53**	**48 878.63**	**48 878.11**
∅ 83				
Lateral outlet Art. # **48 783**	**48 783.51**	**48 783.53**	**48 783.63**	**48 783.11**
Vertical outlet Art. # **48 883**	**48 883.51**	**48 883.53**	**48 883.63**	**48 883.11**
∅ 110				
Lateral outlet Art. # **48 711**	**48 711.51**	**48 711.53**	**48 711.63**	**48 711.11**
Vertical outlet Art. # **48 811**	**48 811.51**	**48 811.53**	**48 811.63**	**48 811.11**

For other combinations and accessories see modular system page 168 - 169

EN 1253-1

* 20 mm threshold / 10 mm threshold