1.8 l/sec / 1.1 l/sec* flow rate
Sealing water height 50 mm

Project drains *Ecoguss* with connection flange — Matrix order system

Drain body	Upper sections			
Ecoguss **with connection flange** for connection to SML-pipe, with odour trap 50 mm	**Shallow bed upper section in ABS,** with mesh fabric	**Shallow bed upper section in ABS,** with mesh fabric	**Upper section in ABS**	**Upper section in ABS**
				
				
∅ 58 / 78 / 83 / 110 B 245 / 134 / 134 / 148 H 120 / 109 / 108 / 92	**With slotted cover** 138 x 138 mm and rim in stainless steel AISI 304, class L 15, screwed	**With design cover *Kessel*** 120 x 120 mm and rim in stainless steel AISI 304, class L 15, *Lock & Lift* System	**With design cover *Kessel*** 120 x 120 mm, and rim in stainless steel AISI 304, class L 15, *Lock & Lift* System	**With slotted cover** 138 x 138 mm in stainless steel AISI 304, class K 3, screwed
	Art. # **48 963**	Art. # **48 904**	Art. # **48 201**	Art. # **48 950**
	▼	▼	▼	▼
∅ 58 / 78 / 83 / 110 H 100 / 110 / 110 / 110				
∅ 58	**Complete drain comprising a combination of the drain body and upper section**			
Lateral outlet Art. # **48 358**	**48 358.51**	**48 358.53**	**48 358.63**	**48 358.11**
Vertical outlet Art. # **48 458**	**48 458.51**	**48 458.53**	**48 458.63**	**48 458.11**
∅ 78				
Lateral outlet Art. # **48 378**	**48 378.51**	**48 378.53**	**48 378.63**	**48 378.11**
Vertical outlet Art. # **48 478**	**48 478.51**	**48 478.53**	**48 478.63**	**48 478.11**
∅ 83				
Lateral outlet Art. # **48 383**	**48 383.51**	**48 383.53**	**48 383.63**	**48 383.11**
Vertical outlet Art. # **48 483**	**48 483.51**	**48 483.53**	**48 483.63**	**48 483.11**
∅ 110				
Lateral outlet Art. # **48 311**	**48 311.51**	**48 311.53**	**48 311.63**	**48 311.11**
Vertical outlet Art. # **48 411**	**48 411.51**	**48 411.53**	**48 411.63**	**48 411.11**

For other combinations and accessories see modular system page 168 - 169

EN 1253-1

* 20 mm threshold / 10 mm threshold