

Twin flap backwater valve *Staufix SWA*

Installation in a concrete slab/floor

Made of polymer, with telescopic upper section for continuous height- and level adjustment.

For installation depth (D) from 486 – 640 mm, Installation area 750 × 750 mm

With surface water tight cover plate class A 15 made of polymer.

Installation kit with choice of cover.

Backwater valve according to EN 13564 Type 2 with two self-closing flaps, one of which can be locked by hand as an emergency closure.

Accessories:

- Extension sections for installation in waterproof concrete see page 36
- Conversion kits see page 37




Outer diameter Ø (mm)	L × H in mm	Art. no.
-----------------------	-------------	----------

With recessed cover for on-site tiling

Ø 110	642 × 394	73 100.10X
Ø 125	645 × 387	73 125.10X
Ø 160	656 × 370	73 150.10X
Ø 200*	720 × 348	73 200.10X

With black cover

Ø 110	642 × 394	73 100.10S
Ø 125	645 × 387	73 125.10S
Ø 160	656 × 370	73 150.10S
Ø 200*	720 × 348	73 200.10S



CE EN 13564 Type 2

* In-/Outlet Ø 200, hydraulics corresponds to Ø 160

Twin flap backwater valve *Staufix SWA*

Installation in an exposed wastewater pipe

Made of polymer, with protective cover.

Backwater valve according to EN 13564 Type 2 with two self-closing flaps, one of which can be locked by hand as an emergency closure.


Accessories:

Conversion kits see page 37



Outer diameter Ø (mm)	L × H in mm	Art. no.
-----------------------	-------------	----------

Ø 110	642 × 422	73 100.10
Ø 125	645 × 422	73 125.10
Ø 160	656 × 422	73 150.10
Ø 200*	720 × 422	73 200.10



CE EN 13564 Type 2

* In-/Outlet Ø 200, hydraulics corresponds to Ø 160