

## Accessories

Pumpfix F / Staufix FKA / Staufix SWA / Controlfix

### Conversion kits

for models made on or after Jan 2011

			Art. no.
<b>Backwater pumping Pumpfix F</b> for installation in a concrete slab/floor	<b>Compatibility:</b> For Ø 110 – Ø 200* <b>Inclusive:</b> Comfort control unit with recessed cover for on-site tiling and drain, <i>Multistop</i> , gasket <b>Cable length:</b> 5 m ↗ <b>Cable extension:</b> See page 36		80 098
<b>Backwater pumping Pumpfix F</b> for installation in an exposed wastewater pipe	<b>Compatibility:</b> For Ø 110 – Ø 200* <b>Inclusive:</b> Comfort control unit <b>Cable length:</b> 5 m ↗ <b>Cable extension:</b> See page 36		80 097
<b>Motorized backwater valve Staufix FKA</b>	<b>Compatibility:</b> For installation in a concrete slab/floor and in an exposed wastewater pipe, for Ø 110 – Ø 200* <b>Inclusive:</b> Comfort control unit <b>Cable length:</b> 5 m ↗ <b>Cable extension:</b> See page 36		80 093
<b>Backwater valve Staufix SWA</b>	<b>Compatibility:</b> For installation in a concrete slab/floor and in an exposed wastewater pipe, for Ø 110 – Ø 200*  * In-/Outlet Ø 200, hydraulics corresponds to Ø 160		80 091

### Rodent / Insect protection

Compatibility see product description

			Art. no.
<b>Rat protection flap</b>	<b>Inclusive:</b> Stainless steel shield <b>Compatibility:</b> <i>Staufix FKA</i> from 01/2011 to 2015 (with flap in pendulum position)		80 037



### Maintenance

for all Staufix backwater valves (Ø 110, Ø 125, Ø 160)

			Art. no.
<b>Testing funnel</b>	<b>Inclusive:</b> Gasket		70 214

### Spigot and Socket



for backwater valves

			Outer diameter Ø (mm)	Art. no.
<b>Spigot</b>	<b>Function:</b> Removable inlets / outlets, can be mounted in various dimensions		Ø 110 Ø 125 Ø 160 Ø 200*	83 081 83 082 83 083 83 084
<b>Socket</b>	<b>Function:</b> Removable inlets / outlets, can be mounted in various dimensions		Ø 110 Ø 125 Ø 160 Ø 200*	83 085 83 086 83 087 83 088

\* In-/Outlet Ø 200, hydraulics corresponds to Ø 160

### Control unit accessories

Compatibility see product description

			Art. no.
<b>Audible alarm</b>	<b>Compatibility:</b> For all control units with SDS function <b>Cable length:</b> 20 m		20 162
<b>Access code potential-free contact</b>	<b>Compatibility:</b> For Comfort control units beginning model year 2017		80 077