

Basement drain

The Universal

The versatile drain with backwater valve.

It couldn't be more flexible. *The Universal* is a versatile basement drain for sewage free wastewater. It is equipped with a backwater valve and a manually lockable emergency closure. *The Universal* has three inlets as a standard feature (two in Ø 50 and one in Ø 75 mm), the telescopic upper section is also rotatable, tiltable and height-adjustable. This ensures it provides maximum flexibility for the design and installation. *The Universal* is optionally available with a slotted grating made of polymer or stainless steel.



1 Drain 2 Inlet 3 Steel cover

Basement drain *The Universal*

For installation in a concrete floor/slab




Made in PP

With lateral outlet 2.5°, 2 inlets Ø 50,
1 inlet Ø 75 mm with blind plug, odour trap
and sludge trap.

With/without twin flap backwater valve.

Drainage capacity 1.8 l/sec flow rate.

Installation area 400 × 320 mm



Cover:

Slotted cover 188 × 188 mm made of
polymer, black, class K 3;

slotted cover 187 × 187 mm and rim made
of stainless steel AISI 304, screwed,
class L 15

➤ **Accessories:** see pages 272 – 273

With twin flap backwater valve

Outer diameter Ø (mm)	Installation depth D in mm	Art. no.
--------------------------	-------------------------------	----------

With black cover

Ø 110	216 - 276	27 611
-------	-----------	--------

With stainless steel cover

Ø 110	216 - 266	27 621
-------	-----------	--------

Without twin flap backwater valve

Outer diameter Ø (mm)	Installation depth D in mm	Art. no.
--------------------------	-------------------------------	----------

With black cover

Ø 110	216 - 276	29 111
-------	-----------	--------

With stainless steel cover

Ø 110	216 - 266	29 121
-------	-----------	--------